10

15

20

25

What Is Claimed Is:

<u>}</u>	A method of providing an answer, in a poorly formalized domain,
to a natural language query, the method comprising the steps of:	
(a)	ouilding a translation formula based on the query;
(b)	natching the translation formula with a semantic header derived
from the doma	n; and
(c)	extracting the answer from the domain.
2.	The method of claim 1, further comprising the step of:
	(d) creating the semantic header for the answer, performed
before step (b).	
3.	The method of claim 2, wherein said step (d) comprises the steps
of:	
	(i) identifying expected queries with respect to the domain;
	(ii) creating a graph of the domain structure;
	(iii) determining subgraphs of the classification graph in
accordance with the expected queries; and	
	(iv) creating a semantic header for each question.
4.	The method of claim 1, further comprising the step of:
	(d) clarifying the query, performed after step (b).
5.	The method of claim 4 wherein said step (d) comprises the steps
of:	
	(i) determining entities, from a predetermined set of entities,
that could instantiate an uninstantiated expression in the translation formula;	
	(ii) presenting the determined entities to a user; and
	(iii) receiving an indication from the user of a chosen entity.

10

15

20

of:

of:

of:

of:

and

6. The method of claim 1, further comprising the steps of: (d) displaying the answer. 7. The method of claim 1, wherein step (a) comprises the steps of: (i) performing concept extraction from the domain, based on the translation formula; and (ii) controlling the generality of the translation formula. 8. The method of claim 7, wherein step (a) further comprises the step (iii) normalizing a word of the translation formula, performed before step (i). 9. The method of claim 7, wherein step (a) further comprises the step (iii) substituting a synonym for a word of the translation formula, performed before step (i). 10. The method of claim 7, wherein step (a) further comprises the step (iii) substituting for a metapredicate in the translation formula, performed after step (i). 11. The method of claim 7, wherein said step (ii) comprises the steps

testing for improper generality of the translation formula;

altering the generality of the translation formula.

(A)

(B)

10

15

20

- 12. The method of claim 11, wherein step (B) comprises the step of attenuating the translation formula.
- 13. The method of claim 12, wherein said step (B) further comprises the step of performing antisymmetric linkage, performed before said attenuating step.
- 14. The method of claim 11, wherein said step (B) comprises the step of argument substitution.
- 15. The method of claim 14, wherein said step (B) further comprises the step of argument extraction, performed before said argument substitution step.
- 16. The method of claim 1, wherein said step (a) comprises the step of processing logical connectives in the translation formula.
- 17. The method of claim 1, wherein said step (a) comprises the step of reordering the predicates of the translation formula according to procedural semantics.
- 18. The method of claim 1, wherein said step (a) comprises the step of performing condition insertion.
- 19. A method of extending a poorly formalized domain, comprising the steps of:
- (a) receiving at least one of a query and an answer from an expert;
- (b) if the query is received, translating the query into at least one semantic header;

10

15

20

- (c) if the query and the answer are received, adding the answer and the corresponding at least one semantic headers to the domain, to form an extended domain; and
 - (d) compiling the extended domain.
- 20. A method of providing a query and answer tool adaptable by a client, comprising the steps of:
 - (a) providing a compiled domain to a client;
- (b) enabling a extension of the domain without the assistance of a knowledge engineer.
- 21. The method of claim 20, wherein said step (b) comprises the step of enabling the client to extend the domain without the assistance of a knowledge engineer.
- 22. The method of claim 20, wherein said step (b) comprises the step of enabling an authorized user of the domain to extend the domain without the assistance of a knowledge engineer.
- 23. A computer program product comprising a computer usable medium having computer readable program code means embodied in said medium for causing an application program to execute on a computer that provides an answer, in a poorly formalized domain, to a natural language query, said computer readable program code means comprising:
- (a) computer readable program code means for causing the computer to build a translation formula based on the query;
- (b) computer readable program code means for causing the computer to match the translation formula with a semantic header derived from the domain; and

25

10

15

20

- (c) computer readable program code means for causing the computer to extract the answer from the domain.
 - 24. The computer program product of claim 23, further comprising:
- (d) computer readable program code means for causing the computer to create the semantic header for the answer.
 - 25. The computer program product of claim 23, further comprising:
- (d) computer readable program code means for causing the computer to clarify the translation formula.
 - 26. The computer program product of claim 23, further comprising:
- (d) computer readable program code means for causing the computer to display the answer.
- 27. The computer program product of claim 23, wherein said computer readable program code means (a) comprises:
- (i) computer readable program code means for causing the computer to perform concept extraction from the domain, based on the translation formula; and
- (ii) computer readable program code means for causing the computer to control the generality of the translation formula.
- 28. A computer program product comprising a computer usable medium having computer readable program code means embodied in said medium for causing an application program to execute on a computer that extends a poorly formalized domain, said computer readable program code means comprising:
- (a) computer readable program code means for causing the computer to receive at least one of an answer and a query from an expert;

- (b) computer readable program code means for causing the computer to translate the answer into at least one semantic header, if an answer is received;
- (c) computer readable program code means for causing the computer to add the answer and the corresponding at least one semantic header to the domain, if a query and answer are received, to form an extended domain; and
- (d) computer readable program code means for causing the computer to compile the extended domain.

SKGF Ref: 1964.0010001